

CLASSIC UNDERLAY

FOR WOOD & LAMINATE FLOORS

3-Way Insulation

Warmer

Keeps cold out & warmth in. 2 Tog



Quieter

Absorbs noise by 20dB



Drier

Non-absorbing



Levels & Supports

Smooths

Levels minor subfloor imperfections



Supports

and braces board joints



Resilient

Withstands high loads < 10T/m²



Durable

Mould resistant



Easy to Install

Lightweight

and easy to cut with a knife



Installation in brief

- Floor should be clean, dry & dust-free.
- Secure loose floorboards and hammer in any protruding nails.
- Lay dry boards in staggered pattern, leaving 5mm gap at room edges.
- Damp-proof membrane to be applied first on damp floors, in cellars & ground floor above unheated rooms.
- Full instructions on back of label.

SPEC

Material	Expanded Polystyrene
Sheet Thickness	6mm
Sheet Dimensions	0.600mm x 0.856mm
Foam Density	32 kg/m ³
Thermal Conductivity	0.030 W/mK
Compression Strength	10 t/m ²
Water absorption	<0.1 vol% Impact
Sound Insulation	20 dB
Fire Protection	Class C Euroclass

20 boards

(60 x 85.6cm each)

= 10.2m² area coverage